


Slide-in coupling

NPUSS



Dimensions



Description

Coupling connector for joining circular ducts.

The product is CE marked according to EN 12101-7 and used in a circular smoke control system - single compartment (see declaration of performance).

Order code

| | |
|---------------------------|-------|
| Product | NPUSS |
| Dimension Ød ₁ | 200 |

Order example: NPUSS-200

| Ød ₁ nom | m kg |
|------------------------|---------|
| 100 | 0,14 |
| 112 | 0,16 |
| 125 | 0,17 |
| 132 | 0,17 |
| 140 | 0,18 |
| 150 | 0,20 |
| 157 | 0,19 |
| 160 | 0,22 |
| 180 | 0,28 |
| 192 | 0,28 |
| 200 | 0,33 |
| 224 | 0,34 |
| 232 | 0,42 |
| 250 | 0,56 |
| 280 | 0,61 |
| 300 | 0,69 |
| 315 | 0,71 |
| 355 | 0,82 |
| 400 | 1,17 |
| 450 | 1,41 |
| 500 | 1,60 |
| 560 | 1,99 |
| 600 | 2,20 |
| 630 | 2,34 |
| 710 | 2,77 |
| 800 | 3,23 |
| 900 | 4,62 |
| 1000 | 5,46 |
| 1120 | 7,32 |
| 1250 | 8,03 |
| 1400 | 13,1 |
| 1500 | 14,2 |
| 1600 | 16,9 |